

Q⁸ LOG OIL

Q⁸ Log Oil for Decks



www.OutlastProducts.com



Finding the right wood stain product can be challenging. Deciding on the correct wood stain color can be just as tricky. Staining a deck is a lot of work, and picking the wrong color creates more work and more expense if you aren't delighted. So before you choose a wood stain, decide if you want your deck to stand out or complement your current color scheme. Now, purchase color samples and test them before investing time and money into a complete treatment. Curing and full-color appearance for Q8 Log Oil can take approximately two weeks. Your deck is a place to gather, and you will need a proven deck to protect your space.

SHADES OF Q⁸

Q⁸ Log Oil is available in a variety of colors.

(01) Natural Base

(02) Light Gold

(03) Medium Gold

(04) Medium Reddish Brown

(05) Dark Brown

(06) Barn Gray



BENEFITS

- Rot control
- Stops decay fungi and mold
- Toxic to termites and powder post beetles
- Superior water repellency
- Beautiful translucent colors
- EPA registered (EPA REG. NO. 81819-1) Wood Preservative • Controls cracking and splitting
- Meets all Federal, State, and Local VOC restrictions
- Pre-tinted colors ideally suited for decks!
- Available in gallons if desired for End-Cut treatment which validates the warranty on Wolmanized, Thompsonized, and Outdoor wood products.
- Available in ALL 50 States!

PROTECTS AGAINST THE ELEMENTS

Your deck must stand up to the elements. Wear and tear can make your deck look old and worn. On the other hand, staining your deck with Q8 Log Oil can give it a new, fresh look.



CHOOSING THE RIGHT TIME

Determining the best time to stain your deck depends on the weather and the time you have to invest. Ideally, you will need at least two days. However, if prep work is involved (e.g., pressure washing, removing boards), this may add time to your project.

Just about anytime when the temperatures are consistently above freezing is an excellent time to think about cleaning your deck. Outlast KleenStart may be suitable for your project, and it is easy to use and cost-effective. When the wood is nice and dry and no rain is in the forecast for the next 36 hours - treat the wood with Outlast Q8. A roller or pump sprayer works well. Apply to the point of refusal, and if excess oil remains after about 20 minutes, mop up the excess. The hotter the weather, the better! Q8 can be applied in direct sunlight because it is not a film former and is self-leveling when applied to the saturation point.



TREATING END CUTS

Even the most durable species of wood can lose resistance to damage with an exposed end cut. This is especially true for pressure treated timber/lumber. Any end cut of wood or timber—be it from shaping, planing, sawing, or installing fasteners—exposes the end grain and makes it susceptible to moisture uptake. This is especially important in exterior construction applications like log homes, wood decks and porches, sidewalls, and cladding.

When moisture is present in wood, it becomes more prone to fungal decay, which leads to an even greater rate of water absorption not just on the exposed end cut but also throughout the board. The end grain cut exposes the central core, which was NOT treated against rot during the factory Chemical Pressure Treating Process. The end grain cut is most susceptible to moisture uptake, which can quickly lead to warping, splitting, termite activity decay, and rot. This is why treatment with Q8 Log Oil is needed to prevent premature deterioration and rot in exterior construction. Stain, beautify, and protect your lumber warranty with ONE soaking coat.



BEFORE YOU START

- Outlast® Q 8 Log Oil goes on dark and lightens significantly as it cures.
- Be aware that when Outlast® Q8 Log Oil is applied and has soaked into the wood, it is permanent in the wood. The surfaces will need to be refreshed for color and water repellency, but the product inside cannot be removed.
- If you want to change the color, be advised that solid colors are not possible in this system. Semi-transparent shades are the only choices available. If you wish to change the shade, you can remove it from the surface by power-washing, then re-apply a different semi-transparent shade of Q8 Log Oil after the initial curing process.

APPLICATION

Always "box" (blend) containers from different lot numbers. Spray, brush, or roll.

Stir product well before use and stir occasionally during application to keep pigments suspended.

If the pigment is difficult to get off the bottom, empty the pail as best you can into a second container. Stir a few ounces of mineral spirits into the pigment settled on the bottom until dissolved. Shake well, then add back to the "batch" and stir again.

The fastest, easiest delivery method is by use of a pump-up type sprayer with plastic or non-corrosive tip (brass tips are NOT recommended.) Airless spray applicators are not recommended due to excessive atomization and subsequent product loss.

Apply as much liquid as the wood will absorb. It is not necessary to "keep a wet edge" or to apply multiple coats or wet-on-wet coats.

It is not necessary to clean out equipment until the job is finished, even if the job takes a week or more to complete! When ready, the equipment can be cleaned with laundry detergent and water or mineral spirits if desired.



GUARANTEED

To never require costly corncob removal. No sanding or sandblasting ever needed for recoats.



GUARANTEED

No lap marks or brush marks. Low-pressure spray application spray to refusal.



GUARANTEED

Easy product to apply.



GUARANTEED

Most complete exterior stain and finish product in a single coat application.



Copyright © 2021 OutlastProducts.com. All Rights Reserved.