Safety Data Sheet

Issue Date: 19-Dec-2011	Revision Date: June 1, 2015		Version 1
	1. IDENTIFICATION		
<u>Product Identifier</u> Product Name	Color Burst		
Other means of identification SDS #	CTA-002		
<u>Recommended use of the chemical</u> Recommended Use	and restrictions on use Color enhancing additive for wood preservative.		
Details of the supplier of the safety Supplier Address CTA Products Group 1899 Kings Castle Drive Southaven, MS 38671 www.OutlastCTA.com	<u>data sheet</u>		
Emergency Telephone Number Company Phone Number Emergency Telephone (24 hr)	Phone: 901-647-6909 Fax: 662-349-2286 INFOTRAC 1-352-323-3500 (International) 1-800-535-5053 (North America)		
	2. HAZARDS IDENTIFICATION		
Appearance Brown viscous liquid	Physical State Liquid	Odor	Mild petrochemical odor
Classification_			
Carcinogenicity		Category 2	
Aspiration toxicity		Category 1	
<u>Signal Word</u> Danger			
Hazard Statements Suspected of causing cancer May be fatal if swallowed and enters a	airways		



<u>Precautionary Statements - Prevention</u> Obtain special instructions before use

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician Do not induce vomiting

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Petroleum distillates, hydrotreated light	64742-47-8	Proprietary
Methanol	67-56-1	Proprietary
Xylene	1330-20-7	Proprietary
Ethylbenzene	100-41-4	Proprietary
Ethyl Alcohol	64-17-5	Proprietary

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

First Aid Measures

General Advice	If exposed or concerned: Get medical advice/attention.
Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin Contact	Wash off immediately with plenty of water. Take off contaminated clothing and wash it before reuse. Discard items which cannot be decontaminated, including leather articles such as shoes, belts and watchbands. If skin irritation persists, call a physician.
Inhalation	Remove to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, give artificial respiration. Get medical attention immediately.
Ingestion	IF SWALLOWED: call a poison control center or physician immediately. Never give anything by mouth to an unconscious person. Do not induce vomiting unless directed by medical personnel. If vomiting occurs, lean patient forward to maintain an open airway & prevent aspiration. Get immediate medical attention.

Most important symptoms and effects

Symptoms	Exposed individuals may experience eye tearing, redness and discomfort. Causes skin irritation. Ingestion may cause irritation of the mucous membranes, esophagus, and stomach. Inhalation may cause irritation of respiratory tract. Prolonged breathing of vapors may cause nausea, headache, weakness and/or dizziness. May cause Central Nervous System (CNS) depression. Skin contact may aggravate an existing dermatitis. Conjuntivitis.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Dry chemical. Foam. Carbon dioxide (CO2). Use water spray to cool fire-exposed containers.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

None known.

Hazardous Combustion Products None known.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Use personal protective equipment as required.

Environmental Precautions	Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See
	Section 12, Ecological Information. See Section 13: DISPOSAL CONSIDERATIONS.

Methods and material for containment and cleaning up

Methods for Containment	Prevent further leakage or spillage if safe to do so.
Methods for Clean-Up	For small spills: recover any free liquid and pick up the remainder with granular clay or sand For large spills: eliminate any sources of ignition and dike the area to contain the spill. Recover as much liquid as possible by use of an explosion-proof sump pump or other similar means. Reuse as much material as possible. Pick up the remainder using granular clay or sand.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Handle in accordance with good industrial hygiene and safety practice. Use personal protection recommended in Section 8. Avoid contact with skin, eyes or clothing. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood.

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep container tightly closed and store in a cool, dry and well-ventilated place. Store in closed containers at temperatures above 50°F/ 10°C. Do not store at temperatures above 120°F. Protect from excessive heat. Drum is not a pressure vessel; never use pressure to empty. Store locked up.
Incompatible Materials	Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Petroleum distillates, hydrotreated light 64742-47-8	100 ppm	500 ppm	-
Methanol 67-56-1	STEL: 250 ppm TWA: 200 ppm S*	TWA: 200 ppm TWA: 260 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 260 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 325 mg/m ³ (vacated) S*	IDLH: 6000 ppm TWA: 200 ppm TWA: 260 mg/m ³ STEL: 250 ppm STEL: 325 mg/m ³
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	-
Ethyl Alcohol 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m ³	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m ³

Appropriate engineering controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits. Local exhaust is suggested for use, where possible, in enclosed or confined spaces. Eyewash stations. Showers.

Individual protection measures, such as personal protective equipment

Eye/Face Protection	Goggles and face shield as needed to prevent eye and face contact.
Skin and Body Protection	Rubber or neoprene gloves. Boots and aprons as needed for protection against spills and/or splashes.
Respiratory Protection	Ensure adequate ventilation, especially in confined areas. In case of inadequate ventilation wear respiratory protection.
General Hygiene Consideration	s Handle in accordance with good industrial hygiene and safety practice. Wash contaminated clothing before reuse.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State Appearance Color

Property_

pН **Melting Point/Freezing Point Boiling Point/Boiling Range** Flash Point **Evaporation Rate** Flammability (Solid, Gas) **Upper Flammability Limits** Lower Flammability Limit Vapor Pressure Vapor Density **Specific Gravity** Water Solubility Solubility in other solvents **Partition Coefficient** Auto-ignition Temperature **Decomposition Temperature Kinematic Viscosity** Dynamic Viscosity **Explosive Properties Oxidizing Properties** Density

Liquid Brown viscous liquid Brown

Values

Not determined Not available Not available > 121 °C / > 250 °F < 1 Liquid-not applicable Not determined Not determined <1 mmHg Unknown 1.20 Insoluble in water Not determined 9.25 Lb/gal

Odor Odor Threshold Mild petrochemical odor Not determined

Remarks • Method

Pensky-Martens Closed Cup (PMCC) (butyl acetate = 1)

(1=Water)

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to Avoid

Keep out of reach of children.

Incompatible Materials

Strong oxidizing agents.

Hazardous Decomposition Products

None known based on information supplied.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information	
Eye Contact	Avoid contact with eyes.
Skin Contact	Avoid contact with skin.
Inhalation	Avoid breathing vapors or mists.
Ingestion	Do not taste or swallow.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Water 7732-18-5	> 90 mL/kg (Rat)	-	-
Petroleum distillates, hydrotreated light 64742-47-8	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.2 mg/L (Rat)4 h
Methanol 67-56-1	= 5628 mg/kg (Rat)	= 15800 mg/kg (Rabbit)	= 83.2 mg/L (Rat)4 h = 64000 ppm (Rat)4 h
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15354 mg/kg (Rabbit)	= 17.2 mg/L (Rat)4 h
Xylene 1330-20-7	= 4300 mg/kg (Rat)	> 1700 mg/kg (Rabbit)	= 5000 ppm (Rat)4 h = 47635 mg/L (Rat)4 h
Ethyl Alcohol 64-17-5	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat)4 h

Information on physical. chemical and toxicological effects

Symptoms

Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen. However, the product as a whole has not been tested. Ethanol has been shown to be carcinogenic in long-term studies only when consumed as an alcoholic beverage. Group 3 IARC components are "not classifiable as human carcinogens".

Chemical Name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7		Group 3		
Ethylbenzene 100-41-4	A3	Group 2B		Х
Ethyl Alcohol 64-17-5	A3	Group 1	Known	Х

ACGIH (American Conference of Governmental Industrial Hygienists) A3 - Animal Carcinogen IARC (International Agency for Research on Cancer) Group 2B - Possibly Carcinogenic to Humans Group 1 - Carcinogenic to Humans Group 3 IARC components are "not classifiable as human carcinogens" NTP (National Toxicology Program) Known - Known Carcinogen OSHA (Occupational Safety and Health Administration of the US Department of Labor) X - Present

Aspiration hazard

May be fatal if swallowed and enters airways.

Numerical measures of toxicity

Not determined

12. ECOLOGICAL INFORMATION

Ecotoxicity

Toxic to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Petroleum distillates, hydrotreated light 64742-47-8		45: 96 h Pimephales promelas mg/L LC50 flow-through 2.2: 96 h Lepomis macrochirus mg/L LC50 static 2.4: 96 h Oncorhynchus mykiss mg/L LC50 static		4720: 96 h Den-dronereides heteropoda mg/L LC50
Methanol 67-56-1		28200: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h Pimephales promelas mg/L LC50 static 19500 - 20700: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 18 - 20: 96 h Oncorhynchus mykiss mL/L LC50 static 13500 - 17600: 96 h Lepomis macrochirus mg/L LC50 flow-through		
Ethylbenzene 100-41-4	4.6: 72 h Pseudokirchneriella subcapitata mg/L EC50 438: 96 h Pseudokirchneriella subcapitata mg/L EC50 2.6 - 11.3: 72 h Pseudokirchneriella subcapitata mg/L EC50 static 1.7 - 7.6: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	11.0 - 18.0: 96 h Oncorhynchus mykiss mg/L LC50 static 4.2: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 7.55 - 11: 96 h Pimephales promelas mg/L LC50 flow-through 32: 96 h Lepomis macrochirus mg/L LC50 static 9.1 - 15.6: 96 h Pimephales promelas mg/L LC50 static 9.6: 96 h Poecilia reticulata mg/L LC50 static	EC50 = 9.68 mg/L 30 min EC50 = 96 mg/L 24 h	1.8 - 2.4: 48 h Daphnia magna mg/L EC50
Xylene 1330-20-7		13.4: 96 h Pimephales promelas mg/L LC50 flow-through 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 flow-through 19: 96 h Lepomis macrochirus mg/L LC50 static 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50 static		3.82: 48 h water flea mg/L EC50 0.6: 48 h Gammarus lacustris mg/L LC50
Ethyl Alcohol 64-17-5		12.0 - 16.0: 96 h Oncorhynchus mykiss mL/L LC50 static 100: 96 h Pimephales promelas mg/L LC50 static 13400 - 15100: 96 h Pimephales promelas mg/L LC50 flow-through	EC50 = 34634 mg/L 30 min EC50 = 35470 mg/L 5 min	9268 - 14221: 48 h Daphnia magna mg/L LC50 10800: 24 h Daphnia magna mg/L EC50 2: 48 h Daphnia magna mg/L EC50 Static

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
Methanol 67-56-1	-0.77
Xylene 1330-20-7	3.15
Ethylbenzene 100-41-4	3.118
Ethyl Alcohol 64-17-5	-0.32

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated Packaging	Disposal should be in accordance with applicable regional, national and local laws and regulations.

US EPA Waste Number

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Methanol 67-56-1		Included in waste stream: F039		U154
Ethylbenzene 100-41-4		Included in waste stream: F039		
Xylene 1330-20-7		Included in waste stream: F039		U239

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Methanol	Toxic
67-56-1	Ignitable
Xylene	Toxic
1330-20-7	Ignitable
Ethylbenzene	Toxic
100-41-4	Ignitable
Ethyl Alcohol	Toxic
64-17-5	Ignitable

14. TRANSPORT INFORMATION

Note	Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.
DOT	Not regulated
IATA	Not regulated
IMDG_ Marine Pollutant	This material may meet the definition of a marine pollutant

15. REGULATORY INFORMATION

International Inventories

Not determined

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

- DSL/NDSL Canadian Domestic Substances List/Non-Domestic Substances List
- EINECS/ELINCS European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
- ENCS Japan Existing and New Chemical Substances
- IECSC China Inventory of Existing Chemical Substances
- KECL Korean Existing and Evaluated Chemical Substances
- PICCS Philippines Inventory of Chemicals and Chemical Substances

US Federal Regulations

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Methanol	5000 lb		RQ 5000 lb final RQ
67-56-1			RQ 2270 kg final RQ
Xylene	100 lb		RQ 100 lb final RQ
1330-20-7			RQ 45.4 kg final RQ
Ethylbenzene	1000 lb		RQ 1000 lb final RQ
100-41-4			RQ 454 kg final RQ

<u>SARA 313</u>

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold
			Values %
Methanol - 67-56-1	67-56-1	Proprietary	1.0
Ethylbenzene - 100-41-4	100-41-4	Proprietary	0.1
Xylene - 1330-20-7	1330-20-7	Proprietary	1.0

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Component	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7 (Proprietary)	100 lb			Х
Ethylbenzene 100-41-4 (Proprietary)	1000 lb	Х	X	Х

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Methanol - 67-56-1	Developmental
Ethylbenzene - 100-41-4	Carcinogen
Ethyl Alcohol - 64-17-5	Carcinogen
	Developmental

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Methanol 67-56-1	Х	Х	Х
Ethylbenzene 100-41-4	Х	X	Х
Xylene 1330-20-7	Х	Х	Х
Ethyl Alcohol 64-17-5	Х	Х	Х

16. OTHER INFORMATION

<u>NFPA</u> HMIS	Health Hazards 2 Health Hazards	Flammability 0 Flammability	Instability 0 Physical Hazards	Special Hazards None Personal Protection
	Not determined	Not determined	Not determined	Not determined
Issue Date:	19-Dec-	2011		
Revision Date:	24-Jan-2	2014		
Revision Note:	New for	mat		

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet